

✘ *pad printing machines*

✘ *pad printing accessories*



**Pad-printing machine  
microPrint ML 350  
closed system  
1 – 4 colours**



- ✘ freely programmable printing positions on x-y-position
- ✘ individually programmable printing sequences and flows
- ✘ set-up time minimization
- ✘ all parameters are storable and retrievable



# Pad-printing machine microPrint ML 350 closed system 1–4 colours



## Technical data

The ML 350 is a precise, compact and robust built pad printing machine for highest demands. The ML 350 is to be used manually as stand machine, or easily can be integrated in fully automatic systems.

clichee size:	max. 300 x 400 mm
ink-cup:	4 x Ø 86 mm, 3 x Ø 120 mm, 2 x Ø 140 mm
max. print image size:	4 x Ø 76 mm, 3 x Ø 110 mm, 2 x Ø 130 mm
cycles:	up to 1,450 per hour
drive:	electro-pneumatic driven
force of pressure:	max. 175 kg
air consumption:	162 l per cycle
pneumatic-supply:	5-6 bar
controlling:	SPS
sizes:	1,065 x 1,630 x 600 (D x H x W)
weight:	360 kg base including



Optional pad shuttle for pad movement



Different print images on cliché



Viscomat: (optionally)

**Scope of delivery:** pad cleaning, ink-cup, cliché holder, foot switch

Tampomark GmbH  
Rheinhorststr. 1-3  
D-67071 Ludwigshafen

Fon: +49 (621) 150328-0  
Fax: +49 (621) 150328-99

info@tampomark.de  
www.tampomark.de



Click here for  
the homepage.  
Just scan with  
your phone.

