

✕ *pad printing machines*

✕ *pad printing accessories*



**Pad-printing machine
microPrint ML 500
closed system
1–4 colours**



- ✕ freely programmable printing positions on x-y-position
- ✕ individually programmable printing sequences and flows
- ✕ set-up time minimization
- ✕ all parameters are storable and retrievable



Pad-printing machine microPrint ML 500 closed system 1–4 colours



Technical data

The ML 500 is a precise, compact and robust built pad printing machine for highest demands. The ML 500 is to be used manually as stand machine, or easily can be integrated in fully automatic systems.

clichee size:	max. 300 x 520 mm
ink-cup:	5 x Ø 86 mm, 4 x Ø 120 mm, 3 x Ø 140 mm
max. print image size:	5 x Ø 76 mm, 4 x Ø 110 mm, 3 x Ø 130 mm
cycles:	up to 900 per hour
drive:	electro-pneumatic driven
force of pressure:	max. 300 kg
air consumption:	39,5 l per cycle
pneumatic-supply:	5-6 bar
controlling:	SPS
sizes:	1,190 x 1,680 x 706 (D x H x W)
weight:	450 kg base including



Optional pad shuttle for pad movement



Different print images on clichee



Viscomat: (optionally)

Scope of delivery: pad cleaning, ink-cup, clichee holder, foot switch

Tampomark GmbH
Rheinhorststr. 1-3
D-67071 Ludwigshafen

Fon: +49 (621) 150328-0
Fax: +49 (621) 150328-99

info@tampomark.de
www.tampomark.de



Click here for
the homepage.
Just scan with
your phone.

